


T	L	Nr zamówieniowy
G1/8	4	80.0176.18
G1/4	6	80.0176.14
G3/8	6	80.0176.38
G1/2	9	80.0176.12
G3/4	10	80.0176.34
G1	10	80.0176.100

Wykonanie materiałowe: mosiądz

80.0176

TŁUMIK HAŁASU WKRĘCANY




T	B	ØD	L	Nr zamówieniowy
M5	4	6,5	23	80.7070.M5
G1/8	6	12,5	34	80.7070.18
G1/4	7	15,5	42,5	80.7070.14
G3/8	11,5	18,5	67,5	80.7070.38
G1/2	11	23,5	78	80.7070.12
G3/4	15,5	38,5	130	80.7070.34
G1	19,5	49	160	80.7070.100

Wykonanie materiałowe: acetylopolimer

80.7070

TŁUMIK HAŁASU




T	PRZEWÓD		B	L	SW	Nr zamówieniowy
	ØDz	ØDw				
G1/4	16	8	10	10	19	60.0061.14.1608
G3/8	18	10	12	12	24	60.0061.38.1810
G1/2	26	16	14	14	27	60.0061.12.2616
G3/4	31	20	16	16	32	60.0061.34.3120

Wykonanie materiałowe: stal cynkowana

60.0061

PRZYŁĄCZKA PROSTA NAKRĘCANA
DO PRZEWODÓW W OPŁOCIE METALOWYM



T	PRZEWÓD		B	L	SW	Nr zamówieniowy
	ØDz	ØDw				
M16x1,5	16	8	18	40	19	60.0062.14.1608
M20x1,5	18	10	21	43	24	60.0062.38.1810
M24x1,5	26	16	21	47	27	60.0062.12.2616
M30x2	31	20	26	53	32	60.0062.34.3120

Wykonanie materiałowe: stal cynkowana

60.0062

PRZYŁĄCZKA PROSTA NAKRĘCANA
DO PRZEWODÓW W OPŁOCIE METALOWYM

