


T	B	d	L	SW	Nr zamówieniowy
G1/8	6	3,2	22	14	60.0101.18
G1/4	8	5,5	27	17	60.0101.14
G3/8	8	8	28	22	60.0101.38
G1/2	10	12	33	27	60.0101.12
G3/4	13	16	40	32	60.0101.34

Wykonanie materiałowe: stal cynkowana

60.0101

ZŁĄCZKA PROSTA




T	B	L	SW	Nr zamówieniowy
M5	4	12	8	80.0120.M5
G1/8	6	17	14	80.0120.18
G1/4	8	21	17	80.0120.14
G3/8	9	23	19	80.0120.38
G1/2	10	26	24	80.0120.12
G3/4	12	30	30	80.0120.34
G1	19	37	34	80.0120.10

Wykonanie materiałowe: mosiądz niklowany

80.0120

ZŁĄCZKA PROSTA




T	B	L1	L2	SW1	SW2	Nr zamówieniowy
R1/8	7	27	9	15	5	80.0400.18
R1/4	11	34	10	19	6	80.0400.14
R3/8	11	37	10	22	8	80.0400.38
R1/2	14	45	12	27	12	80.0400.12
R3/4	16	53	17	36	14	80.0400.34
R1	19	64	20	46	19	80.0400.10

Wykonanie materiałowe: mosiądz

80.0400

PRZYŁĄCZKA PROSTA TYPU NYPEL (ŚRUBUNEK)



T1	T2	B1	B2	L	SW	Nr zamówieniowy
G1/8	M5	5	6	21	14	60.0102.1805
G1/4	G1/8	6	8	26	17	60.0102.1418
G3/8	G1/4	8	8	30	22	60.0102.3814
G1/2	G3/8	8	10	38	27	60.0102.1238
G3/4	G1/2	10	13	40	32	60.0102.3412

Wykonanie materiałowe: stal cynkowana

60.0102

ZŁĄCZKA REDUKCYJNA

