


T	B	L	SW	Nr zamówieniowy
G1/8	7	11	12	80.0131.18
G1/4	11	19	14	80.0131.14
G3/8	11	20	17	80.0131.38
G1/2	14	22	19	80.0131.12

Wykonanie materiałowe: miedź

80.0131

KOREK NAKRĘCANY




T	B	L	SW	Nr zamówieniowy
G1/8	6	8,5	5	81.0132.18
G1/4	8	11	6	81.0132.14
G3/8	9	12,5	8	81.0132.38
G1/2	10	13,5	10	81.0132.12

Wykonanie materiałowe: stal nierdzewna AISI 315

81.0132

KOREK NA IMBUS




T	T1	B	L	SW	Nr zamówieniowy
R1/4	G1/8	11	16	14	81.6208.1418
R3/8	G1/8	11,5	16,5	17	81.6208.3818
R3/8	G1/4	11,5	16,5	17	81.6208.3814
R1/2	G1/4	14	19,5	22	81.6208.1214
R1/2	G3/8	14	19,5	22	81.6208.1238

Wykonanie materiałowe: stal nierdzewna AISI 315

81.6208

REDUKCJA




T	B	L	SW	Nr zamówieniowy
G1/8	6	13	13	80.0172.18
G1/4	7	13	15	80.0172.14
G3/8	8	17	19	80.0172.38
G1/2	10	18	24	80.0172.12
G3/4	10	19	30	80.0172.34

Wykonanie materiałowe: miedź

80.0172

TŁUMIK HAŁASU



T	B	L	SW	Nr zamówieniowy
M5	4	9	8	80.0173.05
G1/8	6	14	13	80.0173.18
G1/4	8	18	16	80.0173.14
G3/8	7	19	19	80.0173.38
G1/2	10	26	24	80.0173.12
G3/4	10	26	30	80.0173.34
G1	10	26	36	80.0173.100

Wykonanie materiałowe: miedź

80.0173

TŁUMIK HAŁASU

