


PRZEWÓD ØDz	ØD	L	Nr zamówieniowy
4	11	31	81.0050.07.04
6	13	35	81.0050.07.06
8	15	37	81.0050.07.08
10	18	42	81.0050.07.10
12	21	48	81.0050.07.12

Wykonanie materiałowe: stal nierdzewna ASI 316L

81.0050.07

ŁĄCZNIK PROSTY WTYKOWY




T	PRZEWÓD ØDz	Smax	L	SW	Nr zamówieniowy
M14x1	6	9,5	35	17	81.0050.08.06
M16x1	8	10,5	37	19	81.0050.08.08
M20x1	10	12,5	42	24	81.0050.08.10
M22x1	12	16,5	48	26	81.0050.08.12

Wykonanie materiałowe: stal nierdzewna ASI 316L

81.0050.08

ŁĄCZNIK GRODZIOWY WTYKOWY




PRZEWÓD ØDz	ØD	L1	L2	SW	Nr zamówieniowy
4	10	36	18	9	81.0050.11.04
6	13	42	21	11	81.0050.11.06
8	15	45	23	12	81.0050.11.08
10	18	52	26	16	81.0050.11.10
12	21	61	31	19	81.0050.11.12

Wykonanie materiałowe: stal nierdzewna ASI 316L

81.0050.11

ŁĄCZNIK WTYKOWY TYPU T




Ø D1	Ø D2	Ø D3	L1	L2	Nr zamówieniowy
4	5	3	28	15	84.8610.04
6	7	3	33	17	84.8610.06
8	9	4	37	18	84.8610.08
10	11	5	42	20	84.8610.10
12	13	6	44	23	84.8610.12

Wykonanie materiałowe: acetylopolimer

84.8610

ZAŚLEPKA DO ZŁĄCZEK WTYKOWYCH



PRZEWÓD ØD	L	Nr zamówieniowy
4	24	80.8610.04
6	25	80.8610.06
8	26	80.8610.08
10	29	80.8610.10
12	31	80.8610.12

Wykonanie materiałowe: poliamid

80.8610

ZAŚLEPKA DO ZŁĄCZEK WTYKOWYCH

