

T	PRZEWÓD ØDz	B	L1	L2	SW1	SW2	Nr zamówieniowy
M5	4	3,5	18	17,5	9	8	80.0050.04.M504
M5	6	3,5	21	20	11	11	80.0050.04.M506
M12x1,25	6	7,5	20	22	11	16	80.0050.04.1206
M12x1,5	6	7,5	20	22	11	16	80.0050.04.1306
M12x1,5	8	7,5	22,5	23,5	12	16	80.0050.04.1308
G1/8	4	5,5	18	18	9	13	80.0050.04.1804
G1/8	6	5,5	21	20	11	13	80.0050.04.1806
G1/8	8	5,5	22,5	22,5	12	13	80.0050.04.1808
G1/4	4	7	18	18	9	16	80.0050.04.1404
G1/4	6	7	21	21,5	11	16	80.0050.04.1406
G1/4	8	7	22,5	23	12	16	80.0050.04.1408
G1/4	10	7	26,5	25,5	14	16	80.0050.04.1410
G1/4	12	8	31,5	27,5	16	20	80.0050.04.1412
G3/8	8	8	22,5	25	12	20	80.0050.04.3808
G3/8	10	8	26,5	25	14	20	80.0050.04.3810
G3/8	12	8	31,5	27	16	20	80.0050.04.3812
G1/2	8	9,5	22,5	26,5	12	25	80.0050.04.1208
G1/2	10	9,5	26,5	26,5	14	25	80.0050.04.1210
G1/2	12	9,5	31,5	28,5	16	25	80.0050.04.1212
G1/2	14	9,5	31,5	29	16	25	80.0050.04.1214

Wykonanie materiałowe: mosiądz niklowany

T	PRZEWÓD ØDz	B	L1	L2	SW	Nr zamówieniowy
R 1/8	4	7	17	16	9	80.0050.05.1804
R 1/8	6	7	21	18	11	80.0050.05.1806
R 1/8	8	7	23	19	13	80.0050.05.1808
R 1/4	6	11	21	22	11	80.0050.05.1406
R 1/4	8	11	23	22	13	80.0050.05.1408
R 1/4	10	11	27	24	16	80.0050.05.1410
R 1/4	12	11	31	28	19	80.0050.05.1412
R 3/8	8	11	25	24	12	80.0050.05.3808
R 3/8	10	11	27	24	16	80.0050.05.3810
R 3/8	12	11	31	28	19	80.0050.05.3812

Wykonanie materiałowe: mosiądz niklowany

T	PRZEWÓD ØDz	B	L1	L2	SW1	SW2	Nr zamówieniowy
G1/8	4	6	17	38	9	13	80.0050.06.1804
G1/8	6	6	21	40	11	16	80.0050.06.1806
G1/8	8	6	23	41	13	13	80.0050.06.1808
G1/4	4	8	17	45	9	16	80.0050.06.1404
G1/4	6	8	21	46	11	16	80.0050.06.1406
G1/4	8	8	23	47	13	16	80.0050.06.1408
G1/4	10	8	27	49	16	16	80.0050.06.1410
G3/8	8	9	23	50	13	18	80.0050.06.3808
G3/8	10	9	27	52	16	18	80.0050.06.3810


Wykonanie materiałowe: mosiądz niklowany

T	PRZEWÓD ØDz	B	L1	L2	SW1	SW2	Nr zamówieniowy
G1/8	4	6	34	23	9	13	80.0050.10.1804
G1/8	6	6	42	25	11	13	80.0050.10.1806
G1/8	8	6	45	26	13	13	80.0050.10.1808
G1/4	6	8	42	28	11	16	80.0050.10.1406
G1/4	8	8	45	29	13	16	80.0050.10.1408
G1/4	10	8	53	31	16	16	80.0050.10.1410
G3/8	8	9	50	25	12	18	80.0050.10.3808
G3/8	10	9	53	33	16	18	80.0050.10.3810
G3/8	12	9	61	36	19	18	80.0050.10.3812

Wykonanie materiałowe: mosiądz niklowany


80.0050.04

PRZYŁĄCZKA KĄTOWA WTYKOWA OBROTOWA




80.0050.05

PRZYŁĄCZKA KĄTOWA WTYKOWA Z GWINTEM STOŻKOWYM



80.0050.06

PRZYŁĄCZKA KĄTOWA WTYKOWA PRZEDŁUŻONA OBROTOWA



80.0050.10

TRÓJNIK WTYKOWY TYPU T OBROTOWY

